

Garmo Adaptive Width Fabric

Lane/cell disable; remap; ordering; bandwidth state; recovery

IP-094 · Architecture IP · Architecture

Function and architecture

- Lane/cell disable
- ordering
- bandwidth state
- recovery

Integration summary

Garmo Adaptive Width Fabric integration role: Service-preserving link-width adaptation. Documented composition: Lane/cell disable; remap; ordering; bandwidth state; recovery.

Technical record

Canonical identity	IP-094
Responsibility	Service-preserving link-width adaptation
Documented building blocks	Lane/cell disable; remap; ordering; bandwidth state; recovery
Delivery boundary	Architecture
Evidence scope	Architecture IP

Delivery and release binding

- Interface version and parameter set
- Clock/reset domains and integration constraints
- Companion memory, PHY and software requirements
- Verification collateral and acceptance criteria

Confirm for the selected release: Node/library binding, Clock/reset limits, Physical and protocol dependencies, Artifact hashes, Acceptance criteria.

Evidence and qualification

Canonical technology and its architecture/integration role are recorded. The offered delivery is confirmed against the exact release before licensing.

No node-port, silicon-performance, standards certification or analog qualification is inherited from a related product.

Canonical status: Engineering build-spec

Source basis: Bible v7.42 IP-094

Evaluation and licensing

Evaluation: Evaluate an individual IP configuration. Production: Named-design production license. Custom work: Node binding or derivative integration. Rights, pricing, support and acceptance criteria are agreed for the exact scope.

Contact: patrick@garmolabs.com | Product path: /ip/garmo-adaptive-width-fabric